



Driven by Performance™

## THE SUPER BRUTE 3500 PSI @ 5.5

### THE SUPER BRUTE

Equipped with a high performance industrial pump driven by a twin cylinder engine, the Super Brute features an adjustable thermostat temperature control. It utilizes a diesel fired burner with automatic electronic ignition, as well as, a double insulated heating coil with a stainless steel housing. Grease, oil and dirt contaminants are easily emulsified and removed with hot water, offering improved results and an efficient cleaning process.

Crafted to provide ease of use along with maintenance, SIMPSON® commercial/industrial pressure washers are well known within the industry for their engineering, design, quality and performance.



#### Pump:

- Belt driven industrial pump
- Axialign™ Adjustment System allows the alignment and maintenance of the high pressure pump to be easily maintained with a single bolt adjustment
- Overpressure safety relief valve
- COMET industrial triplex pump

#### Frame:

- Formed heavy gauge steel base
- 1.5" round tube structural steel
- Powder coated finish for corrosion resistance
- Removable/Reversible foot mounting system

#### Components:

- NEMA 4X electrical enclosure with rocker switch, thermostat control, and hour meter

#### Features:

- 1/2" Schedule 80 coil piping
- Stainless steel coil cover
- Isolated pump & engine plate with vibration dampers

#### Unit Includes:

- 48" Insulated grip wand with 1/4" quick connection
- 3/8" x 50' steel braided Armor Hose™
- 0°, 15°, 25°, 40° and soap quick connect nozzles
- Downstream detergent injector

#### Options:

- Float Tank

MODEL #	ENGINE	PUMP	DRIVE	PSI	GPM	FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	DIMENSIONS
65110	VANGUARD 18HP 570cc	COMET™ Industrial Triplex Pump	BELT	3500	5.5	10 gallon	10 gallon	45.25"W x 41.75"D x 37.125"H

\*Battery not included

FNA GROUP | 7152 99th St., Pleasant Prairie, WI, 53158  
Contact: (847) 348-1500  
www.simpsoncleaning.com

