GP3000i



GP SERIES Inverter Generator

Model 7129-0 UPC: 696471072716

(50-State/CSA)

1 of 2

Features

- PowerRush™ Advanced Technology delivers over 50% more starting capacity allowing you to do more with less*.
- Quiet Inverter Power reduces sound emissions and provides optimal performance.
- True Power™ Technology provides clean, stable power ideal for sensitive electronics, tools and appliances.
- Easy to Carry compact & lightweight design with built-in handle makes transportation easy.
- PowerDial[™] Choke, Run, Off: three operation settings integrated into one simple-to-use dial.
- Economy Mode automatically adjusts engine speed to save fuel and reduce sound emissions.
- **USB Ports** to charge mobile devices including smart phones and tablets.
- Parallel Ready to connect two GP3000i inverter generators for twice the power. (Parallel kit sold separately.)
- Generator Status Lights visual alerts when unit is low on oil, overloaded or ready to use.

*Increases electrical current upon demand; above rated output when starting electric motors.

Model 7668-0 UPC: 696471073102



AC Rated Output Running Watts 2300 AC Maximum Output Starting Watts 3000



Control Panel

GENERAC

50 Amp

120 V

90 Day Limited

90 Day Limited

GP3000i

GP3000i

Length in (mm)

Width in (mm) Height in (mm)

Carton Length in (mm)

Carton Width in (mm)

Carton Height in (mm) Unit Weight Ibs (kg)

Shipping Weight lbs (kg)

Length

2 of 2

Specifications

Product Series	GP3000i		
Model Number	7129-0		
Configuration	50 ST/CSA		
AC Rated Output Running Watts	2300		
AC Maximum Output Starting Watts	3000		
Rated AC Voltage	120 VAC		
Rated AC Frequency	60 Hz		
Rated 120 VAC Amperage	19.1		
Engine Displacement	149cc		
Engine Type	OHV		
Engine RPM	Variable		
Recommended Oil	10W-30 / SAE 30		
Oil Capacity qt (L)	0.6 (0.6)		
Lubrication Method	Splash		
Choke Location	Integrated into PowerDial™		
Fuel Shut Off	Integrated into PowerDial™		
Starting Method	Recoil Pull Start		
Low Oil Shutdown	Yes		
Neutral Bonded to Ground	No		
Floating Neutral	Yes		

Dimensions and Weights

22.2 (565)

13.3 (339)

18.4 (467)

24 (610)

13.8 (350) 21.3 (540)

59.5 (27) 65 (29.5)

Start Switch Type	PowerDial™		
Start Switch Location	On Control Panel		
Fuel Tank Capacity gal (L)	1.06 (4.0)		
Run Time at 50% of Rated Load (Hours)	4.5		
Run Time at 25% of Rated Load (Hours)	5.8		
Warranty- Residential	3 Year Limited		
Warranty- Commercial	1 Year Limited		
Included	Engine oil, oil funnel, tool kit and		
Included	Owner's Manual		
Product Series	Inverter Parallel Kit		
	(sold separately)		
Model	7668-0		
Receptacle Type	(1) 120V 50A 14-50R		
	(1) 120V 30A TT-30R (RV)		

Inverter Parallel Kit (sold separately)				
Length in (mm)	9.84 (250)			
Width in (mm)	4.33 (110)			
Height in (mm)	8.27 (210)			
Carton Length in (mm)	11.02 (280)			
Carton Width in (mm)	9.37 (238)			
Carton Height in (mm)	6.10 (155)			
Unit Weight Ibs (kg)	3.53 (1.6)			
Shipping Weight lbs (kg)	3.8 (1.75)			





0 ...



Width



verter Parallel Kit (sol
ength in (mm)
/idth in (mm)
eight in (mm)
arton Length in (mm)

Rated 120 VAC Amperage

AC Rated Voltage

Warranty- Residential

Warranty- Commercial